DOCKET NO.:AVSI-0010P1/VGXP-0004RESPONSE UNDER 37 C.F.R. §1.116Application No.:10/657,725EXPEDITED PROCEDUREOffice Action Dated:March 15, 2007GROUP ART UNIT 3763

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) An electroporation device comprising:

an electrode assembly having a plurality of needle electrodes for penetrating a selected tissue and delivering an electrical pulse;

a current waveform generator in electrical communication with the plurality of needle electrodes, the waveform generator being capable of generating the electrical pulse;

a power source in electrical communication with the current waveform generator; and

a controller in communication with the current waveform generator and the power source, wherein the controller manages the electroporation procedure and applies electrical energy to the plurality of needle electrodes for a time and under conditions effective to expose adjacent tissue to a substantially constant electrical eurrent; and

a waveform logger in communication with the controller;

wherein the controller is capable of managing the electroporation device to expose tissue adjacent to the needle electrodes to a substantially constant current, the controller is capable of sampling and monitoring the electroporation voltage and current waveforms, and the waveform logger is capable of recording the electroporation voltage and current waveforms. [page 8, para 25; p.17, para 78; p.15, para 73-pg16, para 74 of spec]

- 2. (Canceled)
- 3. (Previously Amended) The device of claim 1, further comprising an impedance tester in electrical communication with the plurality of needle electrodes.
- 4. (Previously Amended) The device of claim 1, further comprising an input device for inputting commands into the controller.

DOCKET NO.: AVSI-0010P1/VGXP-0004

Application No.: 10/657,725

Office Action Dated: March 15, 2007

RESPONSE UNDER 37 C.F.R. §1.116 EXPEDITED PROCEDURE GROUP ART UNIT 3763

5. (Previously Amended) The device of claim 4, wherein the input device is a keypad.

6. (Previously Amended) The device of claim 1, further comprising a status-reporting

device for reporting status information during the electroporation procedure.

7. (Previously Amended) The device of claim 6, wherein the status-reporting device is

an information display panel, an audible notification, a light-emitting diode ("LED"), or a

combination thereof.

8. (Previously Amended) The device of claim 1, further comprising a communications

port in communication with the controller.

9. (Previously Amended) The device of claim 8, wherein the communications port is an

optical serial communications port.

10. (Previously Amended) The device of claim 8, wherein the communications port is an

infrared port.

11. (Previously Amended) The device of claim 1, further comprising memory in

communication with the controller.

12. (Previously Amended) The device of claim 11, wherein the memory is non-volatile.

13. (Previously Amended) The device of claim 1, wherein the power source is a battery.

14. (Previously Amended) The device of claim 1, wherein the electrode assembly further

comprises a handle to which the plurality of needle electrodes are fastened.

Page 3 of 9

DOCKET NO.: AVSI-0010P1/VGXP-0004 RESPONSE UNDER 37 C.F.R. §1.116 EXPEDITED PROCEDURE **Application No.:** 10/657,725 **GROUP ART UNIT 3763**

Office Action Dated: March 15, 2007

15. (Previously Amended) The device of claim 14, wherein the electrode assembly further comprises an activation switch mounted on the handle and in communication with the controller.

16-17. (Cancelled)

- 18. (Previously Amended) The device of claim 1, wherein the plurality of needle electrodes defines a circular array.
- 19. (Previously Amended) The device of claim 18, wherein the circular array is about 1.0 cm in diameter.

20-26. (Canceled)

27. (Currently Amended) A method for electroporating cells of a selected tissue to facilitate the introduction of macromolecules, comprising:

programming an electrical pulse pattern into a controller of an electroporation device, the device comprising the controller, an electrode assembly, a current waveform generator, and a power source;

inserting a plurality of needle electrodes of the electrode assembly having a central channel into the selected tissue, the electrode assembly having a central channel;

measuring the resistance of the plurality of needle electrodes to determine if a circuit can safely be established through the selected tissue;

injecting a solution of the macromolecules into the selected tissue by passing a syringe needle through the central channel and centrally related to of the plurality of needle electrodes;

generating a pulse of electrical energy from the waveform generator in accordance with the programmed electrical pulse patternusing a software based application;

DOCKET NO.: AVSI-0010P1/VGXP-0004 RESPONSE UNDER 37 C.F.R. §1.116 EXPEDITED PROCEDURE **Application No.:** 10/657,725 **GROUP ART UNIT 3763**

Office Action Dated: March 15, 2007

applying the pulse of electrical energy to the plurality of needle electrodes in accordance with the programmed electrical pulse pattern for a time and under conditions effective to expose adjacent the selected tissue to a substantially constant electrical current.

- 28. (Currently Amended) The method of claim 27, further comprising electronically recording data related to the electroporation through a waveform logger in communication with the controller.
- 29. (New) An electroporation device comprising:

an electrode assembly having an electrode disk comprising a plurality of needle electrodes for penetrating a selected tissue and delivering an electrical pulse;

a current waveform generator in electrical communication with the plurality of needle electrodes, the waveform generator being capable of generating the electrical pulse;

a power source in electrical communication with the current waveform generator;

a controller in communication with the current waveform generator and the power source, wherein the controller is comprised of firmware;

<u>and</u>

a waveform logger in communication with the controller;

wherein the controller is capable of sampling and monitoring the electroporation voltage and current waveforms, and the waveform logger is capable of recording the electroporation voltage and current waveforms, and the firmware is capable of managing the waveforms generated by the waveform generator to expose tissue adjacent to the needle electrodes to a substantially constant current.

30. (New) The electroporation device of claim 29, wherein the electrode disk is a replaceable disk.

DOCKET NO.: AVSI-0010P1/VGXP-0004RESPONSE UNDER 37 C.F.R. §1.116**Application No.:** 10/657,725EXPEDITED PROCEDURE**Office Action Dated:** March 15, 2007GROUP ART UNIT 3763

31. (New). The electroporation device of claim 29, wherein the plurality of needle electrodes are spatially arranged in a circular array.